- 1) Productname:
  - Intra Softboard Underlfoor
- 2) Unique indentification code of the product type:
  - **IPUF**
- 3) Intended use:
  - Softboard for internal use as a non-structural component in dry conditions
- 4) Manufacturer/ authorised representative:
  - Houtwerf BV, Produktieweg 62-70, 2382 PD Zoeterwoude, Netherlands
- 5) System of AVCP:
  - System 3
- 6) Harmonised standard:
  - EN 13986:2004 + A1:2015
  - Notified body: Materialprüfungsamt Nordrhein-Westfalen 0432
- 7) Declared Performance(s):

Tab. (1) 1

Essential characteristics	HTS (2)	Performances
Thickness		≤ 10 mm
Reaction to fire, class		E
Water vapour permeability		NDP (3)
Release of formaldehyde		E1
Release (content) of pentachlorophenol (PCP)	EN 13986:2004 + A1:2015	NDP (3)
Airborne sound insulation (surface mass)		NDP (3)
Sound absorption		NDP (3)
Thermal conductivity		0,07 W/(m*K) (EN ISO 14056:2007/AC:2009)
Durability		
Bonding quality		NDP (3)
Internal bond		NDP (3)
Thickness swelling		10%
Moisture resistance		NDP (3)
Bending strength		0,9 N/mm²
Biological durability, use class		1

<sup>(1)</sup> Table

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer / authorised representative by:

Name: P.F. Verbeek

Zoeterwoude

<sup>(2)</sup> Harmonised technical specification

<sup>(3)</sup> No performance determined